



imageRUNNER ADVANCE DX 717/617/527 Series

CONNECT SECURELY, TRANSFORM DIGITALLY

INNOVATIVE SCAN TECHNOLOGY AND SMART SOFTWARE WORK HAND-IN-HAND

The future of business is digital. Canon imageRUNNER ADVANCE DX is a new generation of smart multifunction devices, designed to support and accelerate every step of your digital transformation. Built with Canon's imageRUNNER ADVANCE DNA, state-of-the-art technology and software work hand-in-hand to digitise, automate and optimise content-centric workflows.

Canon's imageRUNNER ADVANCE DX 717/617/527 Series offers smart and secure A4 mono multifunction devices with all-in-one toner cartridges; maximising efficiency, minimising downtime and delivering 360° security. Innovative scanning technology ensures accurate, streak-free scanning at speed, while uniFLOW Online Express (uFOE) cloud software offers streamlined device management and enhanced cloud connectivity as standard. Versatile design supports flexibility and space saving, with counter-top or floor-standing placement suitable for offices with small footprints and high productivity needs.



**CLOUD
CONNECTIVITY**



PRODUCTIVITY



VERSATILE DESIGN



SECURITY  **McAfee
PROTECTED**



SUSTAINABILITY



Canon uniFLOW Online
Outstanding Cloud Output Management Solution



New to the Line

Canon

imageRUNNER ADVANCE DX 717/617/527 Series

CLOUD CONNECTIVITY

- Scan and print documents from any location with enhanced cloud connectivity, offered with re-usable print formats for ease of use
- Cloud-based software-as-a-standard uniFLOW Online Express offers a single integrated solution to enhance device security and simplify print management
- Canon's MEAP platform optimises processes by integrating with document capture and output management solutions and various applications such as uniFLOW Online*, AirPrint, Mopria, Universal Print and Canon PRINT Business

SECURITY

- Ensure information confidentiality and security across the network with IPsec and firewall functionality
- Set up device authentication, two-factor authentication and device function restrictions for both device and cloud-based security measures
- Encrypted PDF scanning ensures document security during scanning process
- Upgrade to uniFLOW Online* for enhanced secure printing, mobile printing, and guest printing from any device

- Combination of Verify system at start up and McAfee Embedded Control software ensures device functionality is never compromised by malware or firmware tampering

PRODUCTIVITY

- Fast, high-quality scanning at 190 ipm (A4) with expansive connectivity options
- Automated scan, store and search workflows boost efficiency and reduce human error
- Device management tools such as iWEMC provide centralised control over the device fleet and print management
- Automatic removal of blank pages when scanning minimises process times
- Reusable formats, automatic file names from barcode data, Office format conversions, and cloud and device OCR with IRIS enable easy handling and fast document processing
- Easily manageable all-in-one toner cartridge replacement, reducing downtime and enabling continuous usage
- Suitable for offices with high-productivity needs, such as governmental bodies, legal firms and real estate agencies

SUSTAINABILITY

- Edit print settings at device-level for accurate scan output
- Quiet operation and reduced paper hitting sounds during scanning is enabled thanks to technologies such as digital registration and a smooth ADF internal structure
- Automated and digitised processes minimise paper usage for a paperless office
- Reduce waste with high-quality scanning, including digital deskewing and advanced stain-resistant glass









VERSATILE DESIGN

- Flexibility with the option of counter-top or floor-standing placement
- Full security functionality without the need for an additional attachment thanks to built-in features like the IC Card Reader for user authentication
- Suitable for offices with small footprints

*uniFLOW Online is available as a Device Based Cloud Subscription for Document Output and Capture Management. Based on business needs, users can upgrade to uniFLOW Online to unlock a range of advanced benefits including: increased security with user authentication methods; personalised workflows to enhance productivity; reduced wastage by releasing jobs at the device; an intuitive cloud dashboard to leverage real-time data; greater control over access and usage to reduce print costs.

NOTE - Certain features are only enabled with the combination of IR ADV DX and uniFLOW Online

QUICK FACTS

-  **Format:** Mono A4
-  **Paper Supply Capacity (Max):** 3,300 sheets
-  **Warm-up time:** 4 seconds or less
-  **Finishing Capabilities:** Collate, Group, Offset*, Staple* (*only available with Finisher models. Offset available with upper tray)
-  **Supported File Types:** PDF, EPS, TIFF, JPEG, and XPS
-  **Print speed:** 52-71 ppm (A4)
-  **Scan speed:** 190 ipm (A4)
-  **Print Languages:** UFR II, PCL6, Adobe® PostScript 3™
-  **Print Resolution:** 600 x 600 to 1,200 x 1,200 (equivalent)

- Enhanced cloud connectivity enables collaborative document access from anywhere, with re-usable formats for easy handling
- Accurate, high-speed scanning is facilitated by Canon's innovative new paper feeding mechanism and stain-resistant glass
- Efficient workflow automation means documents are intuitively scanned, searched and stored with applications including OneDrive, SharePoint, Concur and Dropbox
- McAfee Embedded Control software, alongside other security features, offers complete peace of mind and 360° protection covering document, network and device
- Simplified print management is enabled with centrally-managed print settings and device usage analysis, provided through native uniFLOW Online Express (uFOE)
- Quiet ADF operation, low energy consumption and reduced emissions lower environmental impacts
- Easy, simplified maintenance is enabled with the all-in-one toner cartridge
- Versatile design with counter-top or floor-standing options to fit in any space

TAILORED SOLUTIONS TO MEET EVERY CHALLENGE

CORE

Perform routine office operations safely and with ease, with minimum hardware, embedded software including uFOE and services offering complete device maintenance and support.



HARDWARE



SERVICES



SOFTWARE

BESPOKE

Choose tailored solutions for any business need by removing print management burdens. Consult with Canon experts to manage your extensive requirements, with bespoke solutions and Managed Services options.

ENHANCED

Boost performance with enhancements such as finishing options and security add-ons e.g. Data Removal Service. Choose solutions to expand cloud capabilities with uniFLOW Online including advanced scanning directly with your Google account.

Canon Inc.
canon.com

Canon Europe
canon-europe.com

English edition
© Canon Europa N.V., 2020

EVOLVE YOUR BUSINESS' PRINT ENVIRONMENT WITH SMART, HIGH-SPEED, MONO A4 MULTIFUNCTION DEVICES



Canon uniFLOW Online
Outstanding Cloud Output Management Solution



New to the Line



Canon uniFLOW Online
Outstanding Cloud Output Management Solution




MAIN CONFIGURATION OPTIONS

Choice of paper supply options*



IR-ADV 527i/617i/717i

DESKTOP USE WITHOUT FINISHER



IR-ADV 527iZ/617iZ/717iZ

DESKTOP USE WITH BUILT-IN FINISHER

STANDARD CASSETTE MODULE-AG1

- Media weight 60 to 135 gsm
- 550 sheets (80 gsm)

ENVELOPE CASSETTE MODULE-A1

- Envelope Size COM10 No.10, Monarch, DL, ISO-C5
- Media weight 80 to 100 gsm
- 75 sheets (envelope)

DESKTOP WITH EXTRA CASSETTE (OPTIONAL)

HIGH CAPACITY CASSETTE FEEDING UNIT-D1

- Media weight 60 to 135 gsm
- 2,650 sheets (80 gsm)

STANDARD CASSETTE MODULE-AR1

- Media weight 60 to 135 gsm
- 550 sheets (80 gsm)

PLAIN PEDESTAL TYPE-W2

FLOOR STANDING (OPTIONAL - WITHOUT EXTRA CASSETTE)

PLAIN PEDESTAL TYPE-X2

- For use with 3 (i models) or 2 (iZ models) additional Standard Cassette Feeding Modules AG1

*Paper supply options include up to three additional cassettes for non finisher models (i series) and up to two additional cassettes for finisher models (iZ series)

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the [online product configurator](#).

The Unified Firmware Platform (UFP) ensures that the latest feature upgrades and protection are available, for an enhanced user experience across the entire IR ADVANCE DX portfolio.

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX 527/617/717 Series

MAIN UNIT

Machine type	A4 Monochrome Laser Multifunctional
Core functions	Print, Copy, Scan, Send and optional Fax
Processor	1.75GHz Dual Core Processor
Control Panel	10.1" TFT LCD WSVGA Color Touch panel
Memory	Standard: 3 GB RAM
Hard Disk drive	Standard: 320 GB (available disk space: 250 GB) * A different initial HDD may be used.
Interface Connection	Network Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11b/g/n) Optional: NFC, Bluetooth Low Energy Others Standard: USB 2.0 x 2 (Host), USB 3.0 x 1 (Host), USB 2.0 x 1 (Device) Optional: Copy Control Interface
Paper Supply Capacity (A4, 80 gsm)	Standard: 650 sheets 100-sheets Multi-purpose tray 550-sheets Paper cassette x 1 Maximum: 3,300 sheets (with High Capacity Cassette Feeding Unit-D1)
Paper Output Capacity (A4, 80 gsm)	Standard model (iR-ADV DX 717i/617i/527i): 500 sheets Finisher model (iR-ADV DX 717iZ/617iZ/527iZ): 1,000 sheets
Finishing Capabilities	Standard model (iR-ADV DX 717i/617i/527i): Collate, Group, Offset*, Staple Finisher Model (iR-ADV DX 717iZ/617iZ/527iZ): Collate, Group, Offset*, Staple *available with upper tray
Supported Media Types	Multi-purpose tray: Thin, Plain, Recycled, Heavy, Color, Transparency, Bond, Envelope Paper Cassette: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched
Supported Media Sizes	Multi-purpose tray: Standard size: A4, A5, A5R, A6, B5 Custom size: 76.2 x 127.0 mm to 216.0 x 355.6 mm Envelope: COM10 No.10, Monarch, DL, ISO-C5 Paper Cassette: Standard size: A4, A5, A5R, A6, B5 Custom size: 99.0 x 148.0 mm to 216.0 x 297.0 mm
Supported Media Weights	Multi-purpose tray: 60 to 199 gsm Paper Cassette: 60 to 135 gsm Duplex: 60 to 120 gsm
Warm-up Time	Quick Startup Mode: 4 Seconds or less* *Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display. From Sleep Mode: 10 Seconds or less From Power On: 10 Seconds or Less* *Time from device power on, until copy ready (not print reservation)
Dimensions (W x D x H)	Standard model (iR-ADV DX 717i/617i/527i): 500 x 598 x 617 mm Finisher model (iR-ADV DX 717iZ/617iZ/527iZ): 502 x 598 x 814 mm
Installation Space(W x D)	Standard model/ Finisher model: 1,052 x 823 mm (with left CRG door open + right door open + the cassette drawer open)
Weight	Standard model (iR-ADV DX 717i/617i/527i): Approx. 37 kg including toner Finisher model (iR-ADV DX 717iZ/617iZ/527iZ): Approx. 46 kg including toner

PRINT SPECIFICATIONS

Print Speed*	iR-ADV DX 717i/717iZ 71 ppm (A4), 113 ppm (A5), 40 ppm (A5R, A6) iR-ADV DX 617i/617iZ 61 ppm (A4), 99 ppm (A5), 35 ppm (A5R, A6) iR-ADV DX 527i/527iZ 52 ppm (A4), 80 ppm (A5), 35 ppm (A5R, A6) * 1-sided
Print Resolution (dpi)	600 x 600 to 1,200 x 1,200 (equivalent)
Duplex Print Speed (A4/LTR)	717i/717iZ: 58ipm/62ipm 617i/617iZ: 50ipm/53ipm 527i/527iZ: 50ipm/53ipm
Page description languages	Standard: UFR II, PCL6, Adobe® PostScript®3™
Direct Print	Supported file types: TIFF, JPEG, PDF, EPS, and XPS
Printing from mobile and cloud	AirPrint, Mopria, Universal Print by Microsoft, Canon PRINT Business, and uniFLOW Online A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

Fonts

PS fonts: 136 Roman
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2
*1 Optional PCL International Font Set-A1 is required.
*2 Optional Barcode Printing Kit-D1 is required.

Print Features

Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Toner Reduction, Poster Printing, Forced Hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer

Operating System

UFR II: Windows® 7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X(10.10 or later)
PCL: Windows® 7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019
PS: Windows® 7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X(10.10 or later)
PPD: Windows® 7/8.1/10, Mac OS X(10.9 or later)
McAfee Embedded Control
As of Feb. 2020

COPY SPECIFICATIONS

Copy Speed*

iR-ADV DX 717i/717iZ
71 ppm (A4), 113 ppm (A5), 40 ppm (A5R, A6)
iR-ADV DX 617i/617iZ
61 ppm (A4), 99 ppm (A5), 35 ppm (A5R, A6)
iR-ADV DX 527i/527iZ
52 ppm (A4), 80 ppm (A5), 35 ppm (A5R, A6)
* 1-sided

First-Copy-Out Time (A4)

Approx. 5 seconds or less

Copy resolution (dpi)

600 x 600

Multiple Copies

Up to 9,999 copies

Copy Density

Automatic or Manual (9 Levels)

Magnification

Variable zoom: 25% to 400% (1% Increments)
Preset reduction/enlargement: 25%, 50%, 70%, 100%(1:1), 141%, 200%, 400%

Copy Features

Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Two-sided Original, Job Build, N on 1, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Copy ID Card, Skip Blank Pages, Reserved copy, Copy Sample

SCAN SPECIFICATIONS

Standard type

Single-pass Duplexing Automatic Document Feeder*
[2-sided to 2-sided (Automatic)]
* Detect Feeder Multi Sheet Feed is supported.

Document Feeder Paper Capacity (80 gsm)

100 Sheets

Acceptable Originals and Weights

Platen: Sheet, Book, and 3-Dimensional Objects
Document Feeder media weight:
1-sided scanning: 42 to 128 gsm (BW), 64 to 128 gsm (CL)
2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL)
Note:
Business card: 80 to 220 gsm
Original width narrower than A6: 50 to 128 gsm

Supported Media Sizes

Platen scanning size: up to 216.0 x 355.6 mm
Document Feeder media size:
A4, A5R, A6, B5, Custom size: 48.0 x 128.0 mm to 216.0 x 355.6 mm
Business card: 48.0 x 85.0 mm to 55.0 x 91.0 mm

Scan Speed (ipm; BW/CL, A4)

Send (300 x 300 dpi):
up to 95/190 when Automatic Colour Select "OFF":
1-sided Scanning: 95
2-sided Scanning: 190
Automatic Color Select "ON":
1-sided Scanning: 50
2-sided Scanning: 100
Copy (600 x 600 dpi, BW only):
1-sided Scanning: 95
2-sided Scanning: 140

Scan Resolution (dpi)

Scan for Copy: up to 600 x 600
Scan for Send: (Push) up to 600 x 600 (SMB/FTP/ WebDAV/IFAX), (Pull) up to 600 x 600
Scan for Fax: up to 600 x 600

Pull Scan Specifications

Colour Network ScanGear2. For both TWAIN and WIA
Supported OS: Windows® 7/ 8.1/ 10/ Server2008/ Server2008 R2/ Server2012/ Server2012 R2/ Server 2016
As of Feb. 2020

Scan Method

Push Scan, Pull Scan, Scan to Box, Scan to Advanced Space, Scan to Network, Scan to USB Memory Key, Scan to Mobile devices, Scan to cloud (uniFLOW Online - Optional)



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX 527/617/717 Series

SEND SPECIFICATIONS

Destination	Standard: E-mail/Internet FAX (SMTP), SMB3.0, FTP, WebDAV, Mail Box Optional: G3 FAX, IP Fax
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Send resolution (dpi)	Push: up to 600 x 600 Pull: up to 600 x 600
Communication protocol	File: FTP(TCP/IP), SMB3.0 (TCP/IP), WebDAV E-mail/I-Fax: SMTP, POP3
File Format	Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)
Universal Send Features	Original Type Selection, Two-sided Original, Density Adjustment, Sharpness, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages

FAX SPECIFICATIONS

Maximum Number of Connection Lines	(Optional) 1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400x400 (Ultra Fine), 200x400 (Super Fine), 200x200 (Fine), 200x100 (Normal)
Sending/Receiving Size	A4, A5*, A6* and B5* / A4, A5, B5 *Sent as A4
FAX memory	Up to 30,000 pages (2,000 jobs)
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes
Fax Features	Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log

STORE SPECIFICATIONS

Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes Maximum 30,000 Pages (2,000 jobs) Stored
Advanced Space	Communication Protocol: SMB or WebDAV Supported Client PC: Windows® 8.1/10 Concurrent Connections (Max.): SMB: 64, WebDAV: 3
Advanced Space available disc space	Approx. 16GB
Advanced Space Features	Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support, Search, File Preview, Authentication Management, Open to public, URI TX, Backup/Restore

SECURITY SPECIFICATIONS

Authentication and Access Control	User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print*), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Space Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) *1 Requires uniFLOW Online / uniFLOW

Network Security

Network Security	TLS 1.3, FTPS, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Space in the MFP, Scan and Send -virus Concerns for E-mail Reception
Device Security	Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection), Comply IEEE2600.2 (Common Criteria Certification) (in evaluation)
Device Management and Auditing	Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting Device administration and Security administration Passwords

ENVIRONMENTAL SPECIFICATIONS

Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80 % RH (Relative Humidity) 220-240 V, 50/60 Hz, 4.8 A
Power source	Maximum: Approx. 1,500 W
Power consumption	Copying (with DADF continuous scan): iR-ADV DX 717/717Z: 827.5 W*1 iR-ADV DX 617/617Z: 784.6 W*1 iR-ADV DX 527/527Z: 783.1 W*1 Network Printing: iR-ADV DX 717/717Z: 828.3 W*1 iR-ADV DX 617/617Z: 793.4 W*1 iR-ADV DX 527/527Z: 728.5 W*1 Standby: Approx. 28.92 W*1 Sleep mode: Approx. 1.0 W*2 *1 Reference value: measured one unit *2 1.0 W is not available in all circumstances due to certain settings.

Noise levels

Noise levels	Typical Electricity Consumption (TEC)* rating iR-ADV DX 717/717Z: 0.78 kWh iR-ADV DX 617/617Z: 0.64 kWh iR-ADV DX 527/527Z: 0.54 kWh *As per USA Energy Star 3.0
	Sound Power Level (LWA, m)* Active (I-sided) iR-ADV DX 717Z/717I: 7.0 B, Kv 0.3 B /6.9 B, Kv 0.3 B iR-ADV DX 617Z/617I: 6.8 B, Kv 0.3 B /6.8 B, Kv 0.3 B iR-ADV DX 527Z/527I: 6.8 B, Kv 0.3 B /6.7 B, Kv 0.3 B *Reference value: Measured only one unit with ISO7779, described with ISO9296 (2017)
	Sound Pressure (LpAm)* Bystander's position: Active(BW) (I-sided): iR-ADV DX 717/717Z: 56 dB iR-ADV DX 617/617Z: 55 dB iR-ADV DX 527/527Z: 54 dB Stand-by iR-ADV DX 717Z/617Z/527Z: 25 dB iR-ADV DX 717/617/527I: 21 dB *Reference value: Measured only one unit with ISO7779, described with ISO9296 (2017)

Standards

Standards	Blue Angel
CONSUMABLES	
Toner Cartridges	TO3 Black
Toner Yield	Black: 51,500 pages Toner Cartridge yield in accordance with ISO/IEC 19752.

SOFTWARE AND PRINTER MANAGEMENT

Tracking and reporting	For detailed information please visit our website https://www.canon-europe.com/business/ Universal Login Manager (ULM) uniFLOW Online Express* * For more information, please refer to uniFLOW Online Express uniFLOW Online
Remote management tools	iW Management Console eMaintenance Content Delivery System
Scanning software	Network ScanGear
Platform	MEAP (Multifunctional Embedded Application Platform)
Document Publishing	Kofax PowerPDF (optional)



TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX 527/617/717 Series

PAPER SUPPLY OPTIONS

Cassette Module-AG1

Paper Capacity: 550 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched
Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm
Paper Weight: 60 to 135 gsm
Power Source: From the Main Unit
Dimensions (W x D x H): 484 x 450 x 127 mm (attached to the main unit)
Weight: Approx. 7 kg

Envelope Cassette Module-A1

Paper Capacity: 75 Envelopes
Envelope Size: COM10 No.10, Monarch, DL, ISO-C5
Paper Weight: 80 to 100 gsm
Power Source: From the Main Unit
Dimensions (W x D x H): 484 x 450 x 127 mm (attached to the main unit)
Weight: Approx. 7 kg

Cassette Feeding Unit-AR1

Paper Capacity: 550 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched
Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm
Paper Weight: 60 to 135 gsm
Power Source: From the Main Unit
Dimensions (W x D x H): 642 x 657 x 456 mm (attached to the main unit)
Weight: Approx. 19 kg

High Capacity Cassette Feeding Unit-D1

Upper cassette:
Paper Capacity: 550 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Heavy, Color, Labels, Bond, Pre-punched
Paper Size: A4, A5, A5R, A6, B5, Custom size: 99.0 x 148.0 mm to 216.0 x 355.6 mm
Paper Weight: 60 to 135 gsm

Lower cassette:
Paper Capacity: 2,100 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Heavy, Color, Bond, Pre-punched
Paper Size: A4
Paper Weight: 60 to 135 gsm
Power Source: From the Main Unit
Dimensions (W x D x H): 642 x 657 x 456 mm (attached to the main unit)
Weight: Approx. 27 kg

OUTPUT FEATURES*

Finisher Model (IR-ADV DX 717IZ/ 617IZ/ 527IZ)

*Paper capacity may vary with different paper type/size.

Tray Capacity (80 gsm):
Upper Tray: A4, A5R, B5: 400 sheets
Lower Tray: A4, A5R, B5: 100 sheets
Main unit output tray: A4, A5, A5R, A6, B5: 500 sheets
Paper Type: Thin, Plain, Recycled, Heavy, Color, Bond, Transparency*, Envelope*
*only for Main Unit Output tray
Staple Paper Weight: 60 to 120 gsm
Staple Position: Corner
Staple Paper Size: A4, Custom size (210.0 x 279.4 mm to 216.0 x 355.6 mm)
Staple Capacity: 30 sheets (60 to 90 gsm), 20 sheets (91 to 120 gsm)

HARDWARE ACCESSORIES

Card Readers

Various card readers available e.g. MiCard Plus. Please contact local Canon Office for more details.
Copy Card Reader-F1
Copy Card Reader Attachment-B5

SECURITY OPTIONS

SYSTEM AND CONTROLLER OPTIONS

Print Accessories

PCL International Font Set-A1

Barcode Printing

Barcode Printing Kit-D1

System Accessories

Copy Control Interface Kit-A1
Connection Kit-A2 for Bluetooth LE
NFC Kit-E1

FAX Accessories

Super G3 FAX Board-AY1
Remote Fax Kit-A1
IP FAX Expansion Kit-B1

OTHER OPTIONS

Accessibility Accessories

ADF Access Handle-A1

Consumables

Staple-P1

Software & Solutions



Certifications and compatibility



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2020